

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
①	2	RE-6-3066	YJM	JHW	23.02.23					
APPLICABLE STANDARD										
RATING	OPERATING TEMPERATURE RANGE		-55℃ TO +85℃(note1)			STORAGE TEMPERATURE RANGE		-10℃ TO +60℃		
	VOLTAGE		30 V AC/DC			APPLICABLE CONNECTOR		BK35G06-56DP4-0.35V(***)		
	CURRENT		SIGNAL CONTACT 0.3A POWER CONTACT 2.5A							
SPECIFICATIONS										
ITEM		TEST METHOD				REQUIREMENTS			QT	AT
CONSTRUCTION										
GENERAL EXAMINATION		CONFIRMED VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.			X	X
MARKING		CONFIRMED VISUALLY.							X	X
ELECTRICAL CHARACTERISTICS										
CONTACT RESISTANCE		20mV AC OR LESS 1kHz, 1mA				SIGNAL CONTACT : 50mΩ MAX POWER CONTACT : 30mΩ MAX			X	-
INSULATION RESISTANCE		100V DC				50MΩ MIN			X	-
VOLTAGE PROOF		100V AC FOR 1min.				NO FLASHOVER OR BREAKDOWN			X	-
Voltage Standing Wave Ratio		Frequency 0~5 GHz				VSWR 1.3 Max			X	-
		Frequency 5~10 GHz				VSWR 1.4 Max				
		Frequency 10~20 GHz				VSWR 1.5 Max				
		Frequency 20~40 GHz				VSWR 1.8 Max				
MECHANICAL CHARACTERISTICS										
MECHANICAL OPERATION		10 TIMES INSERTIONS AND EXTRACTIONS.				① CONTACT RESISTANCE: SIGNAL CONTACT : 50mΩ MAX POWER CONTACT : 30mΩ MAX ② NO DAMAGE, CRACK OR LOOSENESS OF PATRS.			X	-
VIBRATION		FREQUENCY 10 TO 55 TO 10 Hz, APPROX 5min SINGLE AMPLITUDE 0.75mm, 10CYCLES, FOR 3 DIRECTIONS.				① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			X	-
SHOCK		490 m/s² DURATION OF PULSE 11ms AT 3 TIMES FOR 3 DIRECTIONS.				① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			X	-
ENVITONMENTAL CHARACTERISTICS										
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55 → +85℃ TIME 30 → 30 min UNDER 5 CYCLES. (RELOCATION TIME TO CHAMBER: WITHIN2~3 MIN)				① CONTACT RESISTANCE: SIGNAL CONTACT : 50mΩ MAX POWER CONTACT : 30mΩ MAX ② INSULATION RESISTANCE: 50MΩ MIN ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			X	-
DAMP HEAT (STEADY STATE)		EXPOSED AT 40±2℃, 90 TO 95%, 96h.				① CONTACT RESISTANCE: SIGNAL CONTACT : 50mΩ MAX POWER CONTACT : 30mΩ MAX ② INSULATION RESISTANCE: 25MΩ MIN ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			X	-
SULPHUR DIOXIDE		EXPOSED IN 25 PPM FOR 96h, 25℃, 75±5%RH. (Test standard : JIS C 60068)				① CONTACT RESISTANCE: SIGNAL CONTACT : 50mΩ MAX POWER CONTACT : 30mΩ MAX ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			X	-
REMARKS					DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED	
Note 1 : INCLUDE THE TEMPERATURE RISING BY CURRENT.					S.G.PARK 22.06.14	S.G.PARK 22.06.14	H.W.JO 22.06.14	H.W.JO 22.06.14		
Unless otherwise specified, refer to JIS C 5402 and IEC 60512										
HIROSE KOREA CO.,LTD.			SPECIFICATION SHEET			PART NO. BK35G06-56DS4-0.35V(800)				
CODE NO.(OLD)		DRAWING NO.			CODE NO.			1/1		
CL		①ELC3-633712-80			①CL 6695-0002-2-800			1/1		