



NOTES

- 1 Fig.1 SHOWS THE STATE APPLICABLE CONTACT ASSEMBLED AND SEQUENTIAL STRUCTURE.
APPLICABLE CRIMPING CONTACT:HR41-SC-1*1(SOLD SAPARATELY)
- 2 APPLICABLE CRIMP CONTACT EXTRACTION TOOL:HR41-TP
- 3 THE RECOMMENDED TIGHTENING TORQUE OF REF. NO. ⑦ AND ⑩ TO BE 5 TO 5.5 N・m
THE ADHESIVE FOR PREVENTION OF LOOSENESS IS NOT NECESSARY IN THE FIRST TIME.
LOCTITE 263, LOCPRIMER 7649, HENKEL JAPAN IS RECOMMENDED TO PREVENT REF NO. ⑦, ⑩ FROM LOOSING. AFTER THE SECOND TIME.
- 4 ROTATION EXAMPLES ARE SHOWN FOR REF.NO. ①, ②, ⑦ AND ⑩.
- 5 Fig.2 SHOWS THE APPEARANCE AFTER ASSEMBLY.
- 6 THE CABLE PULL AND TWISTING STRENGTH AND OTHER CHARACTERISTICS MAY DIFFER, DEPENDING ON THE CABLE STRUCTURE.
PLEASE CONFIRM BEFORE THE USE.
- 7 THE ASSEMBLY OF THIS PRODUCT APPLIES TO THE MANUAL ETAD-C0288

5	SILICONE RUBBER	(LIGHT RED)	10	POLYAMIDE	(BLACK) UL94V-0
4	STAINLESS STEEL		9	POLYAMIDE	(CNC, WHITE) UL94V-0
3	STAINLESS STEEL		8	SILICONE RUBBER	(BLACK)
2	POLYAMIDE	(BLACK) UL94V-0	7	POLYAMIDE	(BLACK) UL94V-0
1	POLYAMIDE	(BLACK) UL94V-0	6	SILICONE RUBBER	(RED)
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS

UNITS mm		SCALE 1 : 1		COUNT 1	DESCRIPTION OF REVISIONS DIS-C-003016	DESIGNED KN. IKEHARA	CHECKED HY. KOBAYASHI	DATE 13. 10. 07
 HIROSE ELECTRIC CO., LTD.		APPROVED : SU. OBARA		13. 01. 28	DRAWING NO. EDC3-118084-00			
		CHECKED : HY. KOBAYASHI		13. 01. 28	PART NO. HR41-25WBPE-3SC			
		DESIGNED : TY. SUZUKI		13. 01. 28	CODE NO. CL141-0024-2-00			
		DRAWN : TY. SUZUKI		13. 01. 28	 0/1			