



CONDITION 1 CONDITION 2 CURRENT VOLTAGE(AC/DC) 600V CURRENT RATING 100A 150A 14 TO 22sq(※1) | 38 TO 50sq(※1) CARLE CREEPAGE DISTANCE(※2) MIN:3.2mm CLEARANCE DISTANCE(※2) MIN:3.2mm

	CONDITION I	CONDITION Ⅲ	CONDITION III		
CURRENT VOLTAGE(AC/DE)	800V	600V	1000V		
	100A(CABLE 14	4 TO 22sq ※ 1)			
CURRENT RATING	125A(CABLE 38sq ※1)				
	150A(CABLE 50sq ※1)				
OVER VOLTAGE CATEGORY	II	Ш			
POLLUTION DEGREE	3				
CREEPAGE DISTANCE(※2)	MIN:12.6mm	MIN:12.6mm	MIN:16mm		
CLEARANCE DISTANCE(%2)	MIN:6mm	MIN:6mm	MIN:8mm		
INSULATION SYSTEM	BASIC INSULAT	TONCPANEL HAS TH	E EARTH)		

№1: AS SCREWS AND CRIMP TERMINAL ATTACHED WITH POWER CONTACT HAVE AN IMPACT ON THE CREEPAGE DISTANCE AND THE CLEARANCE DISTANCE, PLEASE USE RECOMMENDED SCREWS AND CRIMP TERMINALS. IN CASE YOU USE CABLES OTHER THAN FOLLOWING RECOMMENDED SCREWS AND CONTACTS. PLEASE BE CAREFUL THAT THE CREEPAGE DISTANCE AND THE CLEARANCE DISTANCE MEET THE STANDARD OF UL. C-UL. TUV.

№2: THE COVERAGE OF THE CREEPAGE DISTANCE AND THE CLEARANCE DISTANCE IS AS FOLLOWS.

-BETWEEN CRIMP TERMINALS

FORM HC0011-5-8 1

- -BETWEEN POWER CONTACT AND PANEL
- -BETWEEN CRIMP TERMINAL AND PANEL
- -BETWEEN SCREWS (ATTACEHD WITH POWER CONTACT) AND PANEL

1. THE MATING PARTNER OF THIS PRODUCT IS PS3-2UP/12P/16P(**)(CL236-1044-8-**).

2>DRAWING CONTACT No. ARE CORRESPONDING TO CONTACT No. OF PS3-2UP/12P/16P(**). CONTACT No. OF GIBE ARE DIFFERENT FROM DRAWING CONTACT No. (RFFFFR NOTFS No. 4) CONTACT No. OF GT8E REFFERS TO TABLE 1.

3>DRAWING CONTACT No. ARE CORRESPONDING TO CONTACT No. OF PS3-2UP/12P/16P(**). CONTACT No. OF GT8E ARE DIFFERENT FROM DRAWING CONTACT No. (REFFER NOTES No. 4) CONTACT No. OF GT8E REFFERS TO TABLE 2.

4>PLEASE USE THE GT8E BELLOW TO SIGNAL CH OF THIS PRODUCT.

SIGNAL	CN1	GT8E-16DS-HU
SIGNAL	CN2	GT8E-12DS-HU

PLEASE PULL GT8E OUT BY HOLDING DOWN THE LOCK PORTION WHEN EXTRACTION GT8E. PLEASE USE GT8E-2022SCF(01) (GOLD PLATING) CRIMP TERMINAL OF GT8E.

- 5>PLEASE SET THE DISTANCE BETWEEN PANELS AS 24.7 TO 28.7 mm.
- 6>THE TIGHTINING TORQUE FOR THE SCREW ATTACHED WITH REF NO. ② IS 2.5 TO 5.2 N·m. THE RECOMMENDED SCREW AND CRIMP TERMINAL IS AS FOLLOWS.
 - -RECCOMEDNED SCREW: JIS B 1188 SPRING WASHER + CROSS RECESSED PAN HEAD SCREW WITH CAPTIVE POLISHED CIRCULAR WASHER M6 \times 12

-RECOMMENDED CRIMP TERMINAL

CABLE 14sq : JIS C 2805 R14-6 CABLE 22sq : JIS C 2805 R22-6

CABLE 38sq : MANUFACTURED BY NICHIFU CO., LTD R38-6S CABLE 50sg : MANUFACTURED BY NICHIFU CO., LTD R60-6S

7>THE SCREW USED TO ATTACH THE PANEL IS M6. THE TIGHTNING TORQUE FOR SCREW IS 2.5 TO 5.2 N·m.

- 8 > SINCE THE POWER CONTACTS ARE SILVER PLATED, THEY MAY REACT WITH SULFIDE IN THE ATOMOSPHER TO CHANGE THE COLOUR TO BLACKISH BROWN.
- 9 > PLEASE SEE THE FIGURE 1 FOR THE RECOMMENDED PANEL DIMENSION.
- 10>THIS ITEM IS PLANNING TO BE APPROVED BY SASFETY STANDARD(UL.C-UL.TUV STANDARD) UNDER THE CONDITION OF TABLE 3 AND TABLE 4 SAFETY STANDARD IS DEFERRENT UP TO THE APPLIED RATED VOLTAGE AND CURRENT PLEASE SEE THE TABLE 3 AND TABLE 4.
- 11. THE POWER CONTACT OF THIES PRODUCT IS NOT APPLICABLE FOR HOT-SWAP. IT CAN NOT BE USED TO INTERRUPT THE POWER.

		DRAWING NO.	EDC-128099-11-00		
]	PART NO. CODE NO.		PS3-2US/12S/16S(1	1)	
			CL0236-1043-5-11	\bigcirc	$\frac{2}{2}$
	•				