HIROSE ELECTRIC CO., LTD. All Rights Reserved.
May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE













Notes
1. The recommended tightening torque for the Ref No.5 is 5 N・m.
2. This product has floating range of ±2mm from the center of the connector.
3. There are some cases that plating color of Ref No.3 may change from silver to blackish brown due to chemical reaction by sulfre in the atmosphere.
1 4. Busbar and mounting bar shall be either silver plating. Silver plating thickness should be at 3μm min.
5. The recommended distance between installation site and tip of busbar shall be 17.85^{+3}_{0} mm.
1 6. For precautions such as mounting, refer to the technical designation manual ETAD-E3255-00.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
2	Stainless Steel		5	Steel	Nickel Plating : 2μm min
1	PBT	Black, UL94V-0	4	PBT	Black, UL94V-0
			3	Copper Alloy	Silver Plating : 2μm min

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	1 : 1	1	6	DIS-E-00011064	MO. SHIMOYAMA	KG. OKITA	20220909

HIROSE ELECTRIC CO., LTD.

APPROVED	MN. KENJO	20220711
CHECKED	KG. OKITA	20220711
DESIGNED	MO. SHIMOYAMA	20220708
DRAWN	MO. SHIMOYAMA	20220708

DRAWING NO.	EDC-398500-00-00
PART NO.	PS4-6.35T-F19
CODE NO.	CL0236-1087-0-00

1 1/1

FORM HC0011-5-7