APPLICA	BLE STAN	DARD						
Rating	Operating Temperature Range		-°C to -°C	Storage Range	e Temperature	-°C to -°C		
	Voltage		-		Current			
			SPECIFICA	TIO	NS			
ITEM		TEST METHOD			REQUIREMENTS			АТ
CONSTR	RUCTION							
General Examination		Examined visually and with a measuring instrument.			According to drawing.			-
Marking		Confirmed visually.			According to drawing.			-

Supplement : Fluke Networks will guarantee and maintain the product functions of this product.

Please contact Fluke Networks for inquiries regarding this product.

\wedge	COUN	T DESCRIPTION OF REVISIONS	DESIGNED		CHECKED		DA	DATE		
$\overrightarrow{0}$	0									
Note					APPROVED		MN.KENJO	2019	20190515	
						ED	KI.NAGANUMA	NUMA 201905		
							JY.IGA		20190515	
						/N	JY.IGA		20190515	
Note	Note QT:Qualification Test AT:Assurance Test X:Applicable Test				DRAWING NO.		ELC-388328-00-00			
HS.		SPECIFICATION SHEET		PART NO	O		DSX-CHA-5-IX-S			
		HIROSE ELECTRIC CO., LTD.		CODE N	O. CL251-1001-0-00		<u> </u>	1/1		