

1		2			3			4		
△数 COUNT	訂正事項 DISCRIPTION OF REVISIONS	擔當 B Y	檢圖 CHKD	年月日 DATE	△数 COUNT	訂正事項 DISCRIPTION OF REVISIONS	擔當 B Y	檢圖 CHKD	年月日 DATE	
△				. .	△				. .	
△				. .	△				. .	
△				. .	△				. .	

A

B

C

D

E

F

A

B

C

D

E

F

Technical drawing of a connector showing multiple views (top, side, cross-section) with dimensions in mm. Key dimensions include: 0.75 ±0.1, 4.6 ±0.15, 4 ±0.15, 3 ±0.15, 1.4 ±0.15, 2.7 ±0.15, 4 ±0.15, 0.92 ±0.15, 0.7 ±0.15, 4.75 ±0.2, 1.9 ±0.15, 0.8 ±0.15, 0.5 ±0.15, 0.12 ±0.05, 28, 30, and 1.2 ±0.05. A circular feature is labeled with a diameter of 1.2 ±0.05.

参考
1. 1リール当たり 20,000 pcs
2. 適用可能なケーブル : AWG#28, 30

1	COPPER ALLOY	CONTACT : GOLD PLATING 0.76 μm MIN. CARRIER : NICKEL 1.27 μm MIN. OVER NICKEL 1.27 μm MIN.		
NO.	MATERIAL	FINISH,REMARKS		
CODE NO. (OLD)		DRAWN	DESIGNED	CHECKED
		SHIN 22.05.20 J.H	SHIN 22.05.20 J.H	LIM 22.05.20 S.M
		APPROVED		
		LIM 22.05.20 S.M		
		RELEASED		

	DRAWING NO. JDC3-633135-05	PART NO. KW30A-2830PCFA (805)
SCALE 10:1	HIROSE KOREA CO.,LTD.	CODE NO CL 6669-0045-9-805
UNITS mm		1/1

1

2

3

4