May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



1 Recommended panel cutout dimension
3



2

Panel thickness	A
0.5~0.8	33.6
0.9~1.3	34.1
1.4~1.8	34.5
1.9~2.3	34.9









HRS DRAWING FOR REFERENCE

Note 1 Please use non-radius side for the panel hooking area.
2 Applicable panel thicknessing is 2.3 to 0.5 mm.
3 Consult hirose for the other panel cutout designs than recommended one.
4. Per pack : 100 pieces.
△1 5. UL(File No.E52653),
C-UL(File No.E52653) authorization article

NO.	MATERIAL	FINISH , REMARKS
1	PBT	UL94V-0, BLACK

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	△1	1	DIS-H-00004547	TS.MIYAKI	SZ.ONO	20181225

HIROSE ELECTRIC CO., LTD.

APPROVED	HS.OKAWA	20160601
CHECKED	YN.TAKASHITA	20160601
DESIGNED	TT.OHSAKO	20160601
DRAWN	TT.OHSAKO	20160601

DRAWING NO.	EDC-366292-00-00
PART NO.	DF51-24DEP-2C
CODE NO.	CL543-5081-0-00

△1 1/1