




APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO +85 °C	STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C	
	VOLTAGE	AC 100 V	OPERATING HUMIDITY RANGE	RELATIVE HUMIDITY: 95% MAX (NO DEW CONDENSATION IS PERMITTED)	
	CURRENT	SIGNAL: 0.5A			
SPECIFICATIONS					
ITEM		TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION					
GENERAL EXAMINATION		VISUAL AND WITH MEASURING INSTRUMENT	ACCORDING TO A DRAWING	X	X
MARKING		CONFIRM VISUALLY		X	X
ELECTRIC CHARACTERISTICS					
CONTACT RESISTANCE [EIA-364-23]		100 mA	50 mΩ MAX (*1) MATED WITH ER8-100P-0.8SV-**H(**)	X	—
INSULATION RESISTANCE [EIA-364-21]		100 V DC	1000 MΩ MIN	X	—
VOLTAGE PROOF [EIA-364-20]		300 V AC FOR 1 min	NO FLASHOVER OR BREAKDOWN	X	—
MECHANICAL CHARACTERISTICS					
MECHANICAL OPERATION [EIA-364-09]		100 TIMES INSERTION AND EXTRACTION	1) CONTACT RESISTANCE CHANGE: 15 mΩ OR LESS 2) NO FLASHOVER OR BREAKDOWN 3) NO DAMAGE, CRACK OR LOOSENESS OF PARTS	X	—
RANDOM VIBRATION [EIA-364-28]		FREQUENCY: 20 TO 500 Hz POWER SPECTRAL DENSITY: 0.02 G ² /Hz FOR 90 min IN THREE DIRECTIONS	1) NO ELECTRICAL DISCONTINUITY OF 1 μs OR MORE 2) NO DAMAGE, CRACK OR LOOSENESS OF PARTS	X	—
SHOCK [EIA-364-27]		980 m/s ² , DURATION OF PULSE: 6 ms 18TIMES TOTAL, 3 EACH DIRECTION, 3 AXIS		X	—
ENVIRONMENTAL CHARACTERISTICS					
THERMAL SHOCK [EIA-364-32]		TEMPERATURE(°C): -55 → 20 ~ 35 → 85 → 20 ~ 35 TIME(min): 30 → 2 ~ 3 → 30 → 2 ~ 3 UNDER 25 CYCLES	1) CONTACT RESISTANCE CHANGE: 15 mΩ OR LESS 2) NO DAMAGE, CRACK OR LOOSENESS OF PARTS 3) NO FLASHOVER OR BREAKDOWN 4) INSURATION RESISTANCE:1000MΩ MIN	X	—
CYCLIC TEMPERATURE AND HUMIDITY [EIA-364-31]		@ 25 °C, 90-95% RH: 120 min DWELL TIME ↑ ↓ 120min RAMP TIME @ 65 °C, 90-95% RH: 120 min DWELL TIME UNDER 12CYCLES		X	—
DRY HEAT [EIA-364-17]		EXPOSED AT 105 °C, 250 HOURS	1) CONTACT RESISTANCE CHANGE: 15 mΩ OR LESS	X	—
GAS TIGHT [EIA-364-36]		Nitric acid vapor 60min		X	—
Resistance to Soldering Heat [IPC/JEDEC J-STD-020]		Reflow soldering : Peak TMP : 260°C MAX Reflow TMP : 217°C MIN for 40-150sec	No deformation of case of excessive looseness of the terminal.	X	—
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
REMARK (*1) THE VALUE OF CONTACT RESISTANCE INCLUDES THE BULK RESISTANCE. Unless otherwise specified, refer to IEC 60512.			APPROVED	TY. TAKADA	20230418
			CHECKED	TY. TAKADA	20230417
			DESIGNED	KM. KUBOTA	20230417
			DRAWN	KM. KUBOTA	20230417
NOTE -- QT: QUALIFICATION TEST; AT: ASSURANCE TEST; X: APPLICATION TEST			DRAWING NO.	ELC-369145-10-00	
	SPECIFICATION SHEET		PART NO.	ER8-100S-0.8SV-5H (10)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL0625-0034-0-10	 2/1