

Applicable standard					
Rating	Operating Temperature range	-40 °C to +85°C (Note1)	Storage Temperature range	-10 °C to +60°C (Note3)	
	Operating Humidity range	20% to 80% (Note2)	Storage Humidity range	40% to 70% (Note3)	
	Voltage	100V AC/DC	Applicable Connector	DF52#-*P-0.8C	
	Current	AWG 28 : 2.5A AWG 30 : 2.0A AWG 32 : 1.5A	Applicable cablet	AWG28 to AWG32	
Insulation diameter			φ 0.6mm MAX		
Specifications					
Item		Test method	Requirements	QT	AT
Construction					
General examination		Visually and by measuring instrument.	According to drawing.	X	X
Marking		Confirmed visually.		X	X
Electric characteristics					
Contact resistance Millivolt level method		20mV MAX, 1mA (DC or 1000Hz).	10 mΩ MAX.	X	—
Mechanical characteristics					
Mechanical operation		20 times insertion and extraction.	①Contact resistance: 20 mΩ MAX. ②No damage, crack or looseness of parts.	X	—
Vibration		Frequency 10 to 55 Hz, single amplitude 0.75 mm, at 10 cycles for 3 direction.	①No electrical discontinuity of 1 μs. ②No damage, crack or looseness of parts.	X	—
Shock		490 m/s ² duration of pulse 11 ms at 3 times each for 3 both axial directions.	①No electrical discontinuity of 1 μs. ②No damage, crack or looseness of parts.	X	—
Environmental characteristics					
Damp heat (Steady state)		Exposed at 40 ± 2°C , 90 to 95 %, 96 h. (After leaving the room temperature for 1~2h.)	①Contact resistance: 20 mΩ MAX. ②No damage, crack or looseness of parts.	X	—
Rapid change of temperature		Temperature -55°C→ +85°C Time 30min→ 30min Under 5 cycles. (The transferring time of the tank is 2~3 min) (After leaving the room temperature for 1~2h.)	①Contact resistance: 20 mΩ MAX. ②No damage, crack or looseness of parts.	X	—
Note 1: Include the temperature rising by current. Note 2: No condensing Note 3: Apply to the condition of long term storage for unused products before PCB on board. After PCB on board, operating temperature and humidity range is applied for interim strage during transportation.					
	Count	Description of revisions	Designed	Checked	Date
Remarks			Approved	KI. AKIYAMA	14. 11. 18
			Checked	HK. UMEHARA	14. 11. 18
			Designed	TH. YOSHIZAWA	14. 11. 18
			Drawn	TH. YOSHIZAWA	14. 11. 18
Unless otherwise specified, refer to IEC 60512.					
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			Drawing No.	ELC4-361289-00	
	Specification sheet		Part No.	DF52-2832PCF	
	HIROSE ELECTRIC CO., LTD.		Code No.	CL668-0030-5-00	1/1