

May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

1					2					3					4				
COUNT	DESCRIPTION OF REVISIONS			BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS			BY	CHKD	DATE						
△						..	△						..						
△						..	△						..						
△						..	△						..						

Technical drawing of a connector. The drawing includes a top view, a side view, and a cross-section view. Dimensions are provided for various parts of the connector, including lengths, widths, and diameters. A cross-section view shows the internal structure of the connector, including the contact area and the barrel area. The drawing is labeled with 'HRS DRAWING FOR REFERENCE' and '1'.

1.1 REEL CONSISTS OF 2000 CONTACTS.
2. UL (FAIL NO. E52653),
C-UL (FAIL NO. E52653),
TUV (FAIL NO. R9950703) APPROVED PRODUCT.

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
1	COPPER ALLOY	CONTACT AREA: GOLD PLATED 0.2μm min. BARREL AREA (OUTSIDE): TIN PLATED 1μm min. OTHERS: NICKEL PLATED 0.5μm min.			

REMARKS	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
	A. Miura	J. Denfong	H. Umehara	J. Ona	
	'06.07.05	'06.07.05	'06.07.05	'06.07.05	

CODE NO. (OLD) CL	DRAWING NO. EDC4-163661-01	PART NO. DF22A-1416SCFA

SCALE 5 : 1	UNITS mm	CODE NO. CL680-1087-1

FORM NO. 232

TO

