

May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

TO

1			2			3			4		
△の数 COUNT	訂正記事 DESCRIPTION OF REVISIONS	設計 BY	検図 CHKD	年月日 DATE	△の数 COUNT	訂正記事 DESCRIPTION OF REVISIONS	設計 BY	検図 CHKD	年月日 DATE		
△				.	△				.		
△				.	△				.		
△				.	△				.		

Technical drawing of a connector. The main view shows a side profile with dimensions: 17.4 (total length), 8 (distance from front to start of threads), 4.2 (width of front flange), 5 (width of rear flange), 0.6 (height of front flange), 4.4 (height of rear flange), 3.9 (height of front flange at base), and 4.4 (height of rear flange at base). Cross-sections A-A and B-B are shown below. A circular detail view is shown to the left. A watermark 'HRS DRAWING FOR REFERENCE' is overlaid.

1	りん青銅 PHOSPHOR BRONZE	すずめっき TIN PLATED , T=0.25			
部番 NO.	材 質 MATERIAL	処 理 , 備 考 FINISH, REMARKS	部番 NO.	材 質 MATERIAL	処 理 , 備 考 FINISH, REMARKS
備考 REMARKS			製 図 DRAWN	設 計 DESIGNED	検 図 CHECKED
旧製品コード CODE NO.(OLD)			図番 DRAWING NO. EDC4-166263		製品名 PART NO. GT16G- / 1.6-2.9PC
単位 UNITS mm			製品コード CODE NO. CL766-0048-6		1/1