


Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					. .	△					. .
△					. .	△					. .
△					. .	△					. .






PANEL CUTOUT
t = 5 MAX



2 POINTS PRICK PUNCH
IN BOTH FACES.



HRS DRAWING FOR REFERENCE

NOTE 1 THE RECOMMENDED CLAMP TORQUE OF COMPONENT ⑤ : 1.5 TO 2 N·m
LOCTITE 242, LOCTITE OR EQUIVALENT IS RECOMMENDED TO
PREVENT COMPONENT ⑤ FROM LOOSENING.
2 TORQUE FOR THE FIXTURE OF COMPONENT ① AND ③ IS TO BE 0.7 N·m MIN.

NO.	MATERIAL	FINISH , REMARKS
3	POLYACETAL	(WHITE)
2	COPPER ALLOY	SURFACE PLATING : GOLD PLATING 0.2μm min. UNDER PLATING : NICKEL PLATING 3μm min.
1	BRASS	CHROME PLATING

NO.	MATERIAL	FINISH , REMARKS
5	STEEL	NICKEL PLATED
4	POLYAMIDE	(WHITE)

CODE NO. (OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
	E.Yumino 05.09.27	E.Yumino 05.09.27	H.Zemba 05.09.28	M.Sato 05.09.28	

TO
R

SCALE 2 : 1
UNITS mm

DRAWING NO. EDC4-006143-11

PART NO. SR30-10R-4S(11)

HRS HIROSE ELECTRIC CO., LTD.

CODE NO. CL103-0264-0-11

1/1

FORM No. 228