
Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
1	1	DIS-C-000514	T.K	E.K	07.02.17



HRS DRAWING FOR REFERENCE

NOTE: 1 ROTATION TORQUE RESISTANCE OF REF.NO.① AND NO.③ :0.7N·m MIN
2 THE RECOMMENDED CLAMP TORQUE OF REF.NO.④: 1.5N·m
1 3 THE RECOMMENDED CLAMP TORQUE OF REF.NO.⑥: 0.1~0.15N·m
4 LOCTITE 242, LOCTITE OR EQUIVALENT IS RECOMMENDED TO PREVENT REF.NO.④ AND NO.⑥ FROM LOOSENING.
5 ROTATION EXAMPLES OF REF.NO.① AND NO.④ ARE SHOWN.

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
4	BRASS	NICKEL PLATING			
3	POLYACETAL	(WHITE)	7	BRASS	
2	COPPER ALLOY	SURFACE PLATING: GOLD PLATING 0.2μm min. UNDER PLATING: NICKEL PLATING 3μm min.	6	STEEL	NICKEL PLATING M2.6×0.45×3
1	BRASS	CHROME PLATING	5	CR	(BLACK)

CODE NO.(OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
	E.YUMINO 05.09.03	E.YUMINO 05.09.03	H.ZENBA 05.09.09	M.SATO 05.09.12	

TO
R

SCALE 2 : 1
UNITS mm

DRAWING NO. EDC4-008300-71

PART NO. SR30-10JE-4S(71)

HRS HIROSE ELECTRIC CO.,LTD.

CODE NO. CL103-0301-4-71 1/1

FORM NO.228