May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE





Notes
1. Rotation examples of ref. No. ① and ⑥ are shown.
2. The recommended clamp torque of ref. No. ⑩ : 0.2 to 0.3 N・m. LOCTITE 243, HENKEL JAPAN or equivalent is recommended to prevent ref. No. ⑩ from loosening.
3. The recommended clamp torque of ref. No. ⑧ :0.6 to 0.7 N・m.
4. The recommended clamp torque of ref. No. ⑥ : 2 to 3 N・m.
5. Clamp movable range of ref. No. ⑦ max 15, min 8.
6. The cable pull and twisting strength and other characteristics may differ. Plese confirm before the use.

NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
5	BRASS	NICKEL PLATING	10	BRASS	NICKEL PLATING JIS B 1117 M2.6×0.45×2
4	PPS	(BLACK) UL94V-0	9	PHOSPHOR BRONZE	NICKEL PLATING
3	PPS	(BLACK) UL94V-0	8	BRASS	NICKEL PLATING JIS B 1101 M3×0.5×12
2	COPPER ALLOY	SILVER PLATING 5 μm.	7	BRASS	NICKEL PLATING
1	BRASS	NICKEL PLATING	6	BRASS	NICKEL PLATING

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	△0					

HIROSE ELECTRIC CO., LTD.

APPROVED	SU. OBARA	15. 10. 26
CHECKED	HY. KOBAYASHI	15. 10. 26
DESIGNED	KN. IKEHARA	15. 10. 26
DRAWN	KN. IKEHARA	15. 10. 26

DRAWING NO.	EDC-003735-81-00
PART NO.	RM21TP-15S(81)
CODE NO.	CL109-0321-0-81 △0

FORM HC0011-5-51