

1		2		3		4			
COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				
△					△				

MAIN MATING GUIDE

PCB LAYOUT
(INDICATES THE SIDE OF THE SURFACE TO WHICH DIP POSTS ARE INSERTED.)

TM20X2

NOTE 1 THE RECOMMENDED CLAMP TORQUE, REF.NO. ④: 3 TO 4 N·m.
LOCTITE 242, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF.NO. ④ FOR LOOSENING.

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
3	POLYCARBONATE	(BLACK) UL94V-0	5	BRASS	NICKLE PLATING
2	PHOSPHOR BRONZE	SILVER PLATING 4μm min.	4	PHOSPHOR BRONZE	NICKLE PLATING
1	ZINC ALLOY	MATTE FINISH CHROME PLATED			

CODE NO. (OLD)
CL

DRAWN
M. Sato
07.05.31

DESIGNED
T. Morita
07.05.31

CHECKED
E. Kimura
07.06.07

APPROVED
M. Sato
07.06.07

RELEASED

DRAWING NO.
EDC4-007892-71

PART NO.
RM15TRD-10SB(71)

SCALE
2 : 1

UNITS
mm

CODE NO.
CL109-0710-1-71

1
1

HRS
HIROSE ELECTRIC CO., LTD.

FORM NO. 228

TO
R