



- Notes 1 When waterproofing with panel, use Ref. No. 5 (O-ring).
The dimension of attaching Ref. No. 5 to a panel is shown in Fig. 1.
- 2 When mounted on chassis, be careful that Ref. No. 5 is fitted into the indicated groove without any biting.

3	Polyphenylene sulfide	(Black)			
2	Brass	Silver plating 2 μm min.	5	Silicone rubber	(Black)
1	Zinc alloy	Chrome plating	4	Polyphenylene sulfide	(Black)
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS mm		SCALE 2 : 1	COUNT 1	DESCRIPTION OF REVISIONS DIS-C-00016536	DESIGNED TY. SUZUKI
HIROSE ELECTRIC CO., LTD.		APPROVED : TP. KOMATSU	20230613	DRAWING NO.	EDC-111095-81-00
		CHECKED : HY. KOBAYASHI	20230613	PART NO.	RM15WTRZB-4P(81)
		DESIGNED : HT. ZENBA	20230613	CODE NO.	CL0109-1673-2-81
		DRAWN : KR. SUZUKI	20230613		
				DATE	20231208
				CHECKED	HY. KOBAYASHI