

1			2			3			4					
COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△				.	△				.					.
△				.	△				.					.
△				.	△				.					.

MAIN GUIDE

DETAIL OF MOUNTING GUIDE

PANEL CUTOUT
(PANEL THICKNESS 0.7 TO 2)

DIP LOCATION DIMENSION FROM CONNECTOR INTERFACE

MAIN GUIDE

POST DIA (φ 0.55)

NOTE: ① THE RECOMMENDED TIGHTEN TORQUE OF REF.NO. ⑥: 1.5 N·m.
ADHESIVE LOCTITE 242, HENKEL JAPAN LOCTITE OR EQUIVALENT IS RECOMMENDED TO PREVENT REF.NO. ⑥ FROM LOOSENING.

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
3	POLYAMIDE	(BLUE)	6	BRASS	NICKEL PLATED
2	STAINLESS STEEL		5	PHOSPHOR BRONZE	NICKEL PLATED
1	ZINC ALLOY	MATTE FINISH NICKEL PLATED	4	BRASS	OVERPLATING : GOLD 0.2μm min UNDERPLATING : NICKEL 2.0μm min

CODE NO. (OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
	T.SUZUKI	y.y. Yamashita	R. Gawa	M. Saito	
	06.07.22	06.07.22	06.07.22	06.07.22	

SCALE	DRAWING NO.	PART NO.
2 : 1	EDC4-025293-73	HR10-7R-6PA(73)
UNITS	CODE NO.	
mm	CL110-0061-0-73	1/1

HRS HIROSE ELECTRIC CO., LTD.

FORM NO. 228

TO
R