
Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE



NOTES 1 HAND CRIMPING TOOL.REF.NO.⑧:
HR10A-TC-02(CL150-0041-2)
THE HOLE DIAMETER FOR CRIMPING:ϕ5.3
2 THE RECOMMENDED CLAMP TORQUE,
REF.NO.⑥: 1.5 TO 2 N·m.
3 ACROSS FLATS HEXAGON HEAD OF REF.NO.⑦: 1.27
THE RECOMMENDED CLAMP TORQUE,
REF.NO.⑦: 0.3 TO 0.4N·m.
△2 4 LOCTITE 263,HENKEL JAPAN OR EQUIVALENT APPLIES
TO PREVENT REF.NO.①AND⑦FOR LOOSENING.
5 ONE EXAMPLE OF THE ROTATION OF REF.NO.⑥TO
REF.NO.①IS SHOWN.
△2 6 THE ASSEMBLY THIS PRODUCT APPLIES TO
THE MANUAL ETAD-C0354-00.

NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
5	STEEL	NICKEL PLATING			
4	BRASS	MATTE FINISH NICKEL PLATED	9	CR	(BLACK)
3	PHOSPHOR BRONZE	SILVER PLATING 2μm min.	8	BRASS	
2	POLYAMIDE	(BLACK) UL94V-0	7	STEEL	NICKEL PLATING HEXAGON SOCKET SET SCREW M2.6X0.45X2
1	ZINC ALLOY	MATTE FINISH NICKEL PLATED	6	BRASS	NICKEL PLATING

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	△2	2	DIS-C-00016958	HT.ZENBA	EJ.KUNII	20240227

HIROSE ELECTRIC CO., LTD.

APPROVED	MO.SATOH	20051020
CHECKED	EJ.KUNII	20051020
DESIGNED	DS.MATSUNE	20051019
DRAWN	DS.MATSUNE	20051019

DRAWING NO.	EDC4-020535-73
PART NO.	HR10A-7P-4S(73)
CODE NO.	CL0110-0302-5-73 △2 1/1

FORM HC0011-5-51