

1			2			3			4		
COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		
△					△						
△					△						
△					△						

**PCB LAYOUT**  
(INDICATES THE SIDE OF THE SURFACE TO WHICH DIP POSTS ARE INSERTED.)

**DETAIL OF MOUNTING GUIDE**

**PANEL CUTOUT**  
 $t = 0.7 \text{ TO } 2$

**NOTE** ① THE RECOMMENDED CLAMP TORQUE, REF. NO. ⑥ :  $1.5 \text{ N} \cdot \text{m}$ .  
LOCTITE 242, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF. NO. ⑥ FOR LOOSENING.

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
3	POLYBUTYLENE TEREPHTHALATE (BLACK)	UL94V-0	6	BRASS	NICKEL PLATING
2	STAINLESS STEEL		5	PHOSPHOR BRONZE	NICKEL PLATING
1	ZINC ALLOY	MATTE FINISH NICKLE PLATED	4	PHOSPHOR BRONZE	SILVER PLATING $2\mu\text{m min.}$

CODE NO. (OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	<i>M. Sato</i> 07.03.06	<i>T. Kawai</i> 07.03.06	<i>E. Kawai</i> 07.03.08	<i>M. Sato</i> 07.03.08	

SCALE	DRAWING NO.	PART NO.
2 : 1	EDC4-025303-73	HR10A-7R-5SB(73)

UNITS	CODE NO.
mm	CL110-0322-2-73

**HRS** HIROSE ELECTRIC CO., LTD.

TO  
R