

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△						△					
△						△					
APPLICABLE STANDARD											
RATING	OPERATING TEMPERATURE RANGE		-25 °C TO +85 °C			STORAGE TEMPERATURE RANGE		-10 °C TO +60 °C			
	VOLTAGE		AC 100 V , DC 140 V								
	CURRENT		2 A			APPLICABLE CABLE					
SPECIFICATIONS											
ITEM		TEST METHOD				REQUIREMENTS				QT	AT
CONSTRUCTION											
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.				×	×
MARKING		CONFIRMED VISUALLY.								×	×
ELECTRIC CHARACTERISTICS											
CONTACT RESISTANCE		CONTACT SHALL BE MEASURED AT DC 1 A				10 mΩ MAX.				×	×
INSULATION RESISTANCE		100 V DC.				1000 MΩ MIN.				×	×
VOLTAGE PROOF		300 V AC FOR 1 min.				NO FLASHOVER OR BREAKDOWN.				×	×
MECHANICAL CHARACTERISTICS											
CONTACT INSERTION AND WITHDRAWAL FORCES		— BY STEEL GAUGE.				INSERTION AND WITHDRAWAL FORCES : — N MIN.				—	—
CONNECTOR INSERTION AND WITHDRAWAL FORCES		MEASURED BY APPLICABLE CONNECTOR.				INSERTION AND WITHDRAWAL FORCES LOCKING DEVICE WITH LOCK : 70 N MAX.				×	—
MECHANICAL OPERATION		1000 TIMES INSERTIONS AND EXTRACTIONS.				CONTACT RESISTANCE: 15 mΩ MAX.				×	—
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, — m/s ² AT 2 h, FOR 3 DIRECTIONS.				① NO ELECTRICAL DISCONTINUITY OF 10 μs. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.				×	—
SHOCK		490 m/s ² DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.				① NO ELECTRICAL DISCONTINUITY OF 10 μs. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.				×	—
ENVIRONMENTAL CHARACTERISTICS											
DAMP HEAT (STEADY STATE)		EXPOSED AT 40 °C, 90 TO 95 %, 96 h.				① INSULATION RESISTANCE: 5 MΩ MIN (AT HIGH HUMIDITY). ② INSULATION RESISTANCE: 50 MΩ MIN (AT DRY). ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				×	—
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55 → R/T ⁽¹⁾ → +85 → R/T °C TIME 30 → 10 TO 15 → 30 → 10 TO 15 min UNDER 5 CYCLES.				① INSULATION RESISTANCE: 1000 MΩ MIN. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				×	—
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.				NO HEAVY CORROSION.				×	—
DRY HEAT		EXPOSED AT + 85 °C , 96 h.				NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				×	—
COLD		EXPOSED AT - 55 °C , 96 h.				NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				×	—
RESISTANCE TO SOLDERING HEAT		SOLDER TEMPERATURE, + 380 ± 10 °C ,FOR SOLDERING DURATION, 3 ~ 4 s.				NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.				×	—
SOLDERABILITY		SOLDERED AT SOLDER TEMPERATURE, + 350 ± 10 °C FOR SOLDERING DURATION, 2 ~ 3 s.				WETTING ON SOLDER SURFACE, NO SOLDER CLUSTER.				×	—
REMARKS						DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED	
NOTE(1) R/T : ROOM TEMPERATURE						D. Matsune	D. Matsune	E. Kunii	M. Saito		
Unless otherwise specified, refer to JIS C 5402.						'05.10.01	'05.10.01	'05.10.03	05.10.14		
Note QT:Qualification Test AT:Assurance Test ×:Applicable Test											
HRS		HIROSE ELECTRIC CO., LTD.				SPECIFICATION SHEET		PART NO. HR10A-10R-10P(73)			
CODE NO. (OLD)		DRAWING NO.				CODE NO.				1/1	
CL		ELC4-021369-73				CL110-0410-8-73					