


Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.







HRS DRAWING FOR REFERENCE

Notes 1 Across flats hexagon head of REF. NO. ⑧ : 1.27
The concave portion with REF. NO. ⑨ clamped to the cable.
The recommended tightening torque, REF. NO. ⑧ : 0.3 to 0.4 N・m.
△1 LOCTITE 263, HENKEL JAPAN or equivalent applies to prevent REF. NO. ⑧ for loosening.
2 The recommended tightening torque, REF. NO. ⑦ : 2 to 2.5 N・m.
△1 3 LOCTITE 263, HENKEL JAPAN or equivalent applies to prevent REF. NO. ① for loosening.
4 Applicable crimping tool of REF. NO. ⑨ : HR10A-TC-03(CL150-0057-2)
5 One example of the rotation of REF. NO. ⑦ to REF. NO. ① is shown.
6 The cable pull and twisting strength and other characteristics may differ, depending on the cable structure. Please confirm before the use.
△1 7 The assembly this product applies to the manual ETAD-C0354-00.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
5	Brass	Matte finish nickel plated	10	Chloroprene rubber	(Black)
4	Brass	Gold plating 0.2μ min.	9	Brass	
3	Brass	Nickel under plating 2μ min.	8	Steel	Nickel plating M2.6×0.45×3
2	Polyamide	(Black) UL94V-0	7	Brass	Nickel plating
1	Zinc alloy	Matte finish nickel plated	6	Steel	Nickel plating

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	△1	3	DIS-C-00016953	HT. ZENBA	EJ. KUNII	20240220

HIROSE ELECTRIC CO., LTD.

APPROVED	EJ. KUNII	20150929	DRAWING NO. EDC-041593-74-74
CHECKED	EJ. KUNII	20150929	PART NO. HR10A-10PD-12P(74)
DESIGNED	TP. KOMATSU	20150929	
DRAWN	TP. KOMATSU	20150929	CODE NO. CL0110-0448-0-74 △1 1/1