


Jan.1.2022 Copyright 2022 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

1		2			3			4		
COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	
△					△				..	
△					△				..	
△					△				..	



NOTE ① THE RECOMMENDED CLAMP TORQUE, REF. NO. ⑥ : 1.5N · m.  
 LOCTITE 242, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF. NO. ⑥ FOR LOOSENING.

3	POLYAMIDE	(BLACK)	UL94V-0	6	BRASS	NICKEL PLATING
2	STAINLESS STEEL			5	PHOSPHOR BRONZE	NICKEL PLATING
1	ZINC ALLOY	MATTE FINISH	NICKEL PLATED	4	BRASS	SILVER PLATING 2μ m min.
NO.	MATERIAL	FINISH, REMARKS		NO.	MATERIAL	FINISH, REMARKS

CODE NO. (OLD)		DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL		M. Sato	T. Nozaki	E. Kunii	M. Sato	
		07.03.22	07.03.23	07.03.24	07.03.28	
DRAWING NO.			PART NO.			
EDC4-042705-73			HR10G-7R-4P(73)			
UNITS			CODE NO.			
mm			CL110-1602-4-73			1/1

TO
R