

1		2		3		4			
COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				
△					△				

A DETAIL OF MOUNTING GUIDE

PANEL CUTOUT
t=0.7 TO 2

NOTE 1 THE RECOMMENDED CLAMP TORQUE, REF. NO. ⑥ : 1.5N · m.
LOCTITE 242, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO
PREVENT REF. NO. ⑥ FOR LOOSENING.

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
3	POLYAMIDE	(BLACK) UL94V-0	6	BRASS	NICKEL PLATING
2	STAINLESS STEEL		5	PHOSPHOR BRONZE	NICKEL PLATING
1	ZINC ALLOY	MATTE FINISH NICKEL PLATED	4	PHOSPHOR BRONZE	SILVER PLATING 2μ m min.

CODE NO. (OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	M. Sato	T. Nishi	E. Kunita	M. Sato	
	07.03.23	07.03.24	07.03.24	07.03.28	

DRAWING NO.	PART NO.	CODE NO.
EDC4-042708-73	HR10G-7R-6S(73)	CL110-1605-2-73

HRS HIROSE ELECTRIC CO., LTD.

SCALE 2 : 1
UNITS mm

1 2 3 4

TO
R