


Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
1	1	DIS-C-000585	T.K	E.K	07.07.27						. .
											. .
											. .






PANEL CUTOUT
t=0.7 TO 2







B DETAIL OF MOUNTING GUIDE

HRS DRAWING FOR REFERENCE

NOTE 1 THE RECOMMENDED CLAMP TORQUE, REF.NO. ⑦ :2N·m.
LOCTITE 242, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF.NO. ⑦ FOR LOOSENING.

NO.	MATERIAL	FINISH, REMARKS
3	POLYAMIDE	(BLACK) UL94V-0
2	STAINLESS STEEL	
1	ZINC ALLOY	MATTE FINISH NICKEL PLATED

NO.	MATERIAL	FINISH, REMARKS
7	BRASS 1	NICKEL PLATING
6	PHOSPHOR BRONZE	NICKEL PLATING
5	PHOSPHOR BRONZE	OVER PLATING:GOLD 0.2μm min. UNDER PLATING:NICKEL 2μm min.
4	PHOSPHOR BRONZE	

CODE NO.(OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	M.SATO '07 03 26	T.HORII '07 03 27	E.KUNII '07 03 27	M.SATO '07 03 28	

TO
R

SCALE 2 : 1
UNITS mm

DRAWING NO. EDC4-042712-72

PART NO. HR10G-10R-12S(72)

HIROSE ELECTRIC CO.,LTD.

CODE NO. CL110-1609-3-72

1/1

FORM NO.228