


1					2		3		4		
	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
▲	1	DIS-C-000585	T.K	E.K	07.07.27	▲					. .
▲						▲					. .
▲						▲					. .



NOTE 1 THE RECOMMENDED CLAMP TORQUE, REF. NO. ⑦ : 2N · m.
LOCTITE 242, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO
PREVENT REF. NO. ⑦ FOR LOOSENING.

3	POLYAMIDE	(BLACK) UL94V-0	7	BRASS	NICKEL PLATING
2	STAINLESS STEEL		6	PHOSPHOR BRONZE	NICKEL PLATING
1	ZINC ALLOY	MATTE FINISH NICKEL PLATED	5	BRASS	SILVER PLATING: 2μ m min.
			4	BRASS	
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS

CODE NO. (OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	M. SATO	T. HORII	E. KUNII	M. SATO	
	'07 03 23	'07 03 24	'07 03 24	'07 03 28	

DRAWING NO.	PART NO.
EDC4-042713-73	HR10G-10R-12P(73)
UNITS	CODE NO.
mm	CL110-1610-2-73

HRS

HIROSE ELECTRIC CO., LTD.