
Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					. .
△					. .
△					. .



HRS DRAWING FOR REFERENCE

NOTE 1 THE RECONMMENDED CLAMP TORQUE OF REF.NO.⑥ : 1.5N · m .
LOCTITE 242, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF. NO.⑥FROM LOOSENING.

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
3	PBT	(BLACK) UL94V-0	6	BRASS	NICKEL PLATING
2	STAINLESS STEEL		5	PHOSPHOR BRONZE	NICKEL PLATING
1	ZINC ALLOY	MATTE FINISH NICKEL PLATED	4	PHOSPHOR BRONZE	SILVER PLATING 2 μm min.

CODE NO.(OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	H.Kishi 05.09.02	H.Kishi 05.09.02	E.Kunii 05.09.02	M.Sato 05.09.02	

SCALE 2 : 1	DRAWING NO. EDC4-042748-73	PART NO. HR10G-7R-4SB(73)	
UNITS mm	HRS HIROSE ELECTRIC CO.,LTD.	CODE NO. CL110-1801-0-73	1/1

NO	REVISIONS
0	
R	

FORM NO.228