

Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△		-			. .	△					. .
△						△					. .
△						△					. .




PCB LAYOUT


(INDICATES THE SIDE OF THE SURFACE TO WHTCH DIP POSTS ARE INSERTED.)






A DETAIL OF MOUNTING GUIE







PANEL CUTOUT

t 0.7~2

HRS DRAWING FOR REFERENCE

NOTE 1 THE RECONMMENDED CLAMP TORQUE OF REF.NO.⑥ : 1.5N · m .
LOCTITE 242, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF. NO.⑥FROM LOOSENING.

NO.	MATERIAL	FINISH, REMARKS
3	PBT	(BLACK) UL94V-0
2	STAINLESS STEEL	
1	ZINC ALLOY	MATTE FINISH NICKEL PLATED

NO.	MATERIAL	FINISH, REMARKS
6	BRASS	NICKEL PLATING
5	PHOSPHOR BRONZE	NICKEL PLATING
4	PHOSPHOR BRONZE	GOLD PLATING 0.2 μm min. NICKEL UNDER PLATING 2 μm min.

CODE NO.(OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	H.Kishi 05.08.31	H.kishi 05.08.31	E.Yunii 05.09.02	M.Sato 05.09.02	

SCALE 2 : 1	DRAWING NO. EDC4-042752-74	PART NO. HR10G-7R-6SB(74)
UNITS mm	HRS HIROSE ELECTRIC CO.,LTD.	CODE NO. CL110-1805-1-74

1/1

FORM NO.228

TO
R