


Sep.1.2021 Copyright 2021 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



- Notes
- 1 Applicable crimping contact : RP19-SC-222(CL113-0266-2)
(Applicable wire :AWG #24 to #30)
 - △1 2 Applicable crimp contact extraction tool : RP6-SC-TP(CL150-0039-0)
 - 3 This product is delivered disassemble.
 - 4 The cable pull and twisting strength and other characteristics may differ,
Depending on the cable structure. please confirm before the use.

4	Brass					
3	Polycarbonate	(Black)	UL94V-0	7	Flexible polyvinylchloride	(Black)
2	Polycarbonate	(Black)	UL94V-0	6	Brass	Black chromate treatment(Trivalent chromium) JIS B1111 M2×0.4×4
1	Polycarbonate	(Black)	UL94V-0	5	Steel	Nickel plating
NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS

UNITS mm		SCALE 2 : 1	COUNT △ 1	DESCRIPTION OF REVISIONS DIS-C-00001221	DESIGNED MM. ISHII	CHECKED EJ. KUNII	DATE 16.10.18
APPROVED :MR. YOSHIDA 05.01.05				DRAWING NO. EDC4-022069-71			
CHECKED :MO. SATOH 05.01.05				PART NO. RP13A-12PD-20SC(71)			
DESIGNED :YH. YAMADA 05.01.05				CODE NO. CL113-0214-9-71			
DRAWN :YH. YAMADA 05.01.05				△ 1/1			