

Oct.1.2021 Copyright 2021 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD					
RATING	Operating temperature range	-10 °C TO +60 °C	Storage temperature Range	-10 °C TO +60 °C	
	Voltage	AC 100 V , DC 140 V	_____	_____	
	Current	_____	Applicable cable	φ7	
<b>SPECIFICATIONS</b>					
ITEM	TEST METHOD		REQUIREMENTS	QT	AT
<b>CONSTRUCTION</b>					
General examination	Visually and by measuring instrument.		According to drawing.	X	X
Marking	Confirmed visually.			X	X
<b>ELECTRIC CHARACTERISTICS</b>					
Contact resistance	Contact shall be measured AT DC 1 A		15 mΩ MAX.	X	-
Insulation resistance	250 V DC.		1000 mΩ MIN.	X	X
Voltage proof	300 V AC. for 1 min.		No flashover or breakdown.	X	X
<b>MECHANICAL CHARACTERISTICS</b>					
Contact insertion and withdrawal forces	_____ By steel gauge.		Insertion and withdrawal forces : — N MIN.	-	-
Connector insertion and withdrawal forces	Measured by applicable connector.		Insertion and withdrawal forces Locking device with lock : 50 N MAX.	X	-
Mechanical operation	1000 times insertions and extractions.		Contact resistance: 20 mΩ MAX.	X	-
Vibration	Frequency: 10 TO 55 Hz, Single amplitude 0.75 mm, _____ m/s <sup>2</sup> AT 2 h, for 3 directions.		①No electrical discontinuity of 10 μs. ②No damage, crack and looseness of parts.	X	-
Shock	490 m/s <sup>2</sup> duration of pulse 11 ms AT 3 times for 3 directions.		①No electrical discontinuity of 10 μs. ②No damage, crack and looseness of parts.	X	-
Contact retention force	Applying a pull force the wire after the applicable crimped contact is assembled the body.		20 N MIN.	X	-
<b>ENVIRONMENTAL CHARACTERISTICS</b>					
Damp heat (steady state)	Exposed at 40 °C, 90 TO 95 %, 96 h.		①Insulation resistance: 10 MΩ MIN. (At high humidity). ②Insulation resistance: 100 MΩ MIN. (At dry). ③No damage, crack and looseness of parts.	X	-
Rapid change of temperature	Temperature -55 → R/T <sup>(1)</sup> → +85 → R/T °C time 30 → 10 TO 15 → 30 → 10 TO 15 min under 5 cycles.		①Insulation resistance: 100 mΩ MIN. ②No damage, crack and looseness of parts.	X	-
Corrosion salt mist	Exposed in 5 % salt water spray for 48 h.		No heavy corrosion ruin the function.	X	-
Dry heat	Exposed AT + 85 °C , 96 h.		No damage, crack and looseness of parts.	X	-
Cold	Exposed AT - 55 °C , 96 h.		No damage, crack and looseness of parts.	X	-
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
①					
REMARK			APPROVED	EJ. KUNII	16.05.31
(1) R/T : Room temperature The std. Value above indicates at the state applicable contact assembled.			CHECKED	EJ. KUNII	16.05.31
			DESIGNED	MM. ISHII	16.05.31
Unless otherwise specified, refer to IEC 60512 (JIS C 5402).			DRAWN	MM. ISHII	16.05.31
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.	ELC-023501-71-00	
<b>HRS</b>	SPECIFICATION SHEET		PART NO.	RP13A-12JK-15PC (71)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL113-0218-0-71	① 1/1