


Oct.1.2021 Copyright 2021 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



- Notes
- 1 This product is delivered disassemble.
 - 2 Applicable crimping contact :
 Contact No.1 to 11 : RP13A-SC-222(CL113-0151-0)
 (Applicable wire :AWG #24 to #28)
 Contact No.12 to 13 : RP13A-SC-212(CL113-0150-8)
 (Applicable wire :AWG #18 to #22)
 - 3 Applicable crimp contact extraction tool : RP13A-SC-TP(CL150-0022-8)
 - 4 Applicable crimp contact crimping tool : RP13A-TC-02(CL150-0071-3)

4	Brass						
3	Polycarbonate	(Black)	UL94V-0	7	Polyvinylchloride (Black)		
2	Polycarbonate	(Black)	UL94V-0	6	Brass	Black chromate treatment(Trivalent chromium) JIS B1111 M2×0.4×4	
1	Polycarbonate	(Black)	UL94V-0	5	Steel	Nickel plating	
NO.	MATERIAL	FINISH	REMARKS	NO.	MATERIAL	FINISH	REMARKS

UNITS mm	SCALE 2 : 1	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
HIROSE ELECTRIC CO., LTD.			APPROVED :EJ. KUNII 16.03.23 CHECKED :EJ. KUNII 16.03.23 DESIGNED :MM. ISHII 16.03.23 DRAWN :MM. ISHII 16.03.23	DRAWING NO. EDC-041727-71-00 PART NO. RP13A-12PS-13SC(71) CODE NO. CL113-1026-4-71	1/1	