

May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

1		2		3		4	
A						A	
B						B	
C						C	
D						D	
E						E	
F						F	

Notes

- ① The recommended clamp trque of REF. No ① to be 2 to 2.5 N · m.
LOCTITE 263, HENKEL JAPAN or equicalent is recommended to prevent
REF. No. ① form loosening.
- ② The recommended clamp trque of REF. No. ④ to be 0.65 to 0.7 N · m.
- ③ Sealing and airtightness and oil resisting shall be tested
under mated condition with an applicable connector.

2	POLYPHENYLENE SULFIDE	(BLACK)	UL94V-0	4	STAINLESS STEEL	M3×0.5×8
1	BRASS	BLACK CHROME PLATING		3	ACRYLONITRILE BUTADIENE RUBBER	(GRAY)
NO.	MATERIAL	FINISH	REMARKS	NO.	MATERIAL	FINISH . REMARKS

UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
-------------	--	----------------	-----------	--------------------------	----------	---------	------

**HIROSE
ELECTRIC
CO., LTD.**

APPROVED	HY. KOBAYASHI	18. 02. 26
CHECKED	HY. KOBAYASHI	18. 02. 26
DESIGNED	TH. KAMEYA	18. 02. 23
DRAWN	MK. INOUE	18. 02. 13

DRAWING NO.	EDC-110595-31-00
PART NO.	JR13WCC-5(31)
CODE NO.	CL114-2046-3-31

1	1
---	---

FORM HC0011-5-51

2

3

4