May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



HRS DRAWING FOR REFERENCE

Notes 1 The recommended clamp trque of REF. No ① to be 2 to 2.5 N・m.
LOCTITE 263, HENKEL JAPAN or equicalent is recommended to prevent REF. No.① form loosening.
2 The recommended clamp trque of REF. No.④ to be 0.65 to 0.7 N・m.
3 Sealing and airtightness and oil resisting shall be tested under mated condition with an applicable connector.

NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
2	POLYPHENYLENE SULFIDE	(BLACK) UL94V-0	4	STAINLESS STEEL	M3×0.5×8
1	BRASS	BLACK CHROME PLATING	3	ACRYLONITRILE BUTADIENE RUBBER	(GRAY)

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	0					

HIROSE ELECTRIC CO., LTD.

APPROVED	HY. KOBAYASHI	18. 02. 26
CHECKED	HY. KOBAYASHI	18. 02. 26
DESIGNED	TH. KAMEYA	18. 02. 23
DRAWN	MK. INOUE	18. 02. 13

DRAWING NO.	EDC-110599-31-00
PART NO.	JR13WCC-9(31)
CODE NO.	CL114-2050-0-31

0 1/1

FORM HC0011-5-51