APPLICA	BLE STAN	DARD											
RATING	OPERATING TEMPERATURE	RANGE	−25 °C TO +85	°C	STOR RANG		MPERATURE		-10	°C TO	+60	°C	
	VOLTAGE		-									_	
	CURRENT						ICABLE CABLE φ10±0.5mm						
			SPEC	IFIC <i>P</i>	ATIOI	NS							
ITEM CONSTRUCTION		TEST METHOD				REQUIREMENTS							АТ
GENERAL EXAMINATION		VISUALLY		ACCORDING TO DRAWING.						Х	X		
MARKING		CONFIRMED VISUALLY.										_	_
ENVIRONMENTAL		CHARACTERISTICS											
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 500 h.				NO HEAVY CORROSIN RUIN THE FUNCTION.						Х	_
SEALING (1)		EXPOSED AT A DEPTH OF 1.8 m FOR 48 h.				NO WATER PENETRATION INSIDE CONNECTOR.						Х	_
AIRTIGHTNESS(1)		APPLY AIR PRESSURE 18 kPa FOR 30 sec TO INSIDE CONNECTOR.				NO AIR BUBBLES INSIDE CONNECTOR.						Х	_
COUN	IT DE	ESCRIPTI	ON OF REVISIONS		DESIG	SNED			CHEC	KED		DA	TE
<u>A</u>							 						
REMARK	NG AND AIDTICHT	NESS SHALL BE TESTED BY APPLICABLE CONNECTOR AND (O CABLE.		APPRO'			BAYASHI		18.0	
NUIE (I) SEALI	NG AND AIKIIGHII						DESIGN			BAYASHI			2. 26
l Inlana st	norwina ana	cified refer to IIS C 5402 (IEC 60512)								KAMEYA			2. 24
			ied, refer to JIS C 5402.(IEC 60512 AT:Assurance Test X:Applicable Test			DRAWING NO.			MK. INOUE 18. 02. 14 ELC-110459-31-00				
нs		PECIF	PART		JR13WCCA-10 (31)								
NO		HIROSE ELECTRIC CO., LTD.				NO.	CI	<u> </u>			Δ	1/1	
	<u> </u>		JUDE NO.		32111 2010 1 01				_				