APPLICA	BLE STAN	DARD											
RATING	OPERATING TEMPERATURE RANGE		−35 °C TO +85	°C	STORA RANGE		PERATURE		-10	°C TO	+60	°C	
	VOLTAGE				-				_			-	
	CURRENT			_	APPLI	CABLE	CABLE					-	
			SPEC	IFIC A	AOITA	IS							
17	EM		TEST METHOD				REC	UIRE	MENTS			QT	АТ
	UCTION	1											
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.						Х	Χ
MARKING		CONFIRMED VISUALLY.										Х	Х
ENVIRO	MENTAL	CHAR	ACTERISTICS		I							<u> </u>	
SEALING (1)		EXPOSED AT A DEPTH OF 1 m FOR 0.5 h.				NO WATER PENETRATION INSIDE CONNECTOR.						Х	_
AIRTIGHTNESS ⁽¹⁾		APPLY AIR PRESSURE 18 kPa FOR 0.5min TO INSIDE CONNECTOR.				NO AIR BUBBLES INSIDE CONNECTOR.						Х	_
COUN	T DE	ESCRIPTI	ON OF REVISIONS		DESIGN	SNED		CHECKED				DA	ΓΕ
REMARK]		I			TA NO	DAVACIIT		1F 00	0 04
	ING AND AIRTIG	HTNESS SHAI	TNESS SHALL BE TESTED BY APPLICABLE CONNECTOR.			APPROVED CHECKED DESIGNED		_	HY. KOBAYASHI HY. KOBAYASHI			15. 08 15. 08	
									TH. KAMEYA			15. 08	
			fied, refer to IEC 60512.			DRAWN			TH. KAMEYA			15. 08	
							G NO.		ELC-119052-00-00				
HS.		SPECIFICATION SHEET				NO.	JR13WRC5				ı	<u> </u>	
HIR		OSE ELECTRIC CO., LTD.			CODE NO.		CL114-2105-0-00 🔝						1/1