APPLIC/	ABI	LE STANI	DARD											
	01	PERATING		-25 °C TO +	85 °C	STO	DRAGE TEM	MPERATURE		-10	°C TO	+60	°C	
RATING	TI	EMPERATURE	RANGE			RAN	NGE	E						
	۷	OLTAGE				-				-			_	
	CI	URRENT		-		APF	PLICABLE	CABLE					_	
				SPE(CIFICA	ATIC	NS							
	ITE	M			REQUIREMENTS						АТ			
CONSTRUCTION				TEST METHOD									QT	1
GENERAL EXAMINATION			VISUALLY AND BY MEASURING INSTRUMENT.					ACCORDING TO DRAWING.						Х
MARKING			CONFIRMED VISUALLY.					NG TO DIVANT	illu.				X	X
			CHARACTERISTICS										1	1
CORROSION SALT MIST								VY CORROS	ION	RIIIN THE F	UNCTIO	N	Х	
SEALING (1)								NO HEAVY CORROSION RUIN THE FUNCTION. NO WATER PENETRATION INSIDE CONNECTOR.						
A I RT I GHTNESS (1)								NO AIR BUBBLES INSIDE CONNECTOR.						<u> </u>
ATATION NECO			CONNECTOR.					DODDLLO		DE COMMECT	OII.		X	
COU	NT	DE	SCRIPTI	ON OF REVISIONS		DESI	IGNED			CHECK	ŒD		DA	\TE
۵														
REMARK								APPROV	ED	HVKO	DAVACI	⊔ī	10 (22.26
NOTE(1) SEALING AND AIRT			IGHTNESS SHALL BE TESTED BY APPLICABLE CONNECTOR.					_		BAYASI			02.26	
			IGHTNESS SHALL DE TESTED DI AFFLICADLE CONNECTOR.					DESIGNED			BAYASI			02.26
											TH.KAMEYA			02.24
Unless otherwise specified, refer to JIS C 5402 (IEC60512).						DRAWN				INOUE)2.14	
							RAWING NO. ELC-1130							
HS		OF EON TOTAL OFFICE					RT NO.			JR16WRC (31)				
11.7		HIR	OSE ELECTRIC CO., LTD.			CODE		NO. CL11		4-2162-4-31			Ø	1/1