

May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

1		2		3		4		
A							A	
B							B	
C							C	
D							D	
<p>NOTES 1. The recommended clamp torque to receptacle: 1.2N · m 2. In order to prevent screw loosening after assembly to the receptacle, wrap self-fusing tape around this component and the receptacle for stabilization. ⚠ 3. This product is a cap for JR※25WR※-※(※). It is applicable regardless of given alphabets and/or numbers shown at ※.</p>								
1 Polyamide (BLACK) UL94V-0		2 Silicone Rubber (Red brown)						
NO. MATERIAL FINISH . REMARKS		NO. MATERIAL FINISH . REMARKS						
UNITS mm		SCALE 2 : 1	COUNT 1	DESCRIPTION OF REVISIONS DIS-C-002972		DESIGNED WR. AJIRO	CHECKED TP. KOMATSU	DATE 13. 03. 25
HIROSE ELECTRIC CO., LTD.		APPROVED : SU. OBARA 10. 11. 04		DRAWING NO. EDC4-116400-00				
		CHECKED : HY. KOBAYASHI 10. 11. 04		PART NO. JR25WRC5				
		DESIGNED : HS. NAGANO 10. 11. 02		CODE NO. CL114-2175-6-00				
		DRAWN : HS. NAGANO 10. 11. 02		1/1				
FORM HC0011-5-51		2		3		4		