



Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.










PANEL CUTOUT
(t=1 TO 3)



HRS DRAWING FOR REFERENCE

NOTES
1 THE RECOMMENDED CLAMP TORQUE OF REF. NO.⑦ : 3 TO 4 N·m
1 LOCTITE 263 HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF. NO. ⑦ FROM LOOSENING.
1 2 MAKE SURE THAT REF. NO.⑤ DOES NOT HAVE ANY FACTORS TO REDUCE WATER-RESISTANCY, SUCH AS SCRATCH, TWIST, PINCHING, OR DUST.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
4	BERYLLIUM COPPER	SILVER PLATING 2μm min.			
3	BERYLLIUM COPPER	SILVER PLATING 2μm min.	7	BRASS	NICKEL PLATING
2	POLYBUTYLENE TEREPHTHALATE	(BLACK) UL94V-0	6	BRASS	NICKEL PLATING
1	ZINC ALLOY	NICKEL PLATING	5	SILICONE RUBBER	(BLACK)

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	1	4	DIS-C-003146	DS. MATSUNE	HY. KISHI	13. 07. 17

HRS HIROSE ELECTRIC CO., LTD.

APPROVED	MO. SATOH	06. 11. 07	DRAWING NO. EDC3-043815-73
CHECED	EJ. KUNII	06. 11. 06	PART NO. HR22-12WTRA-20S(73)
DESIGNED	HS. KAWASHIMA	06. 11. 02	
DRAWN	MK. SATO	06. 10. 25	CODE NO. CL122-0014-0-73 1 1/1