


Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
1	1	DIS-C-000585	T.K	E.K	07.07.27						. .
					. .						. .
					. .						. .








PANEL CUTOUT
PANEL THICKNESS : 0.7~2





NOTES 1 THE RECOMMENDED TIGHTENING TORQUE OF REF. No.⑥ TO BE 1 N·m.
COATING WITH LOCTITE 242 MANUFACTURED BY HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT LOOSENESS.
2 CONTACT AREA : GOLD 0.2μm min.
TERMINAL AREA : GOLD FLASH.
UNDER PLATING : NICKEL 2μm min

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
3	PHOSPHOR BRONZE	2	6	BRASS 1	NICKEL PLATED
2	PPS	(BLACK) 94V-0	5	PHOSPHOR BRONZE	NICKEL PLATED
1	ZINC ALLOY	MATE FINISH NICKEL PLATED	4	BERYLLIUM COPPER	NICKEL PLATED

CODE NO.(OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	Y.YAMADA '05 11 05	Y.YAMADA '05 11 05	T.AKIYAMA '05 11 05	M.SATO '05 11 05	. .

TO
R

SCALE 5 : 1
UNITS mm

DRAWING NO. EDC3-114769
PART NO. HR25A-7R-6S
HIROSE ELECTRIC CO., LTD
CODE NO. CL125-0603-0
1/1

HRS DRAWING FOR REFERENCE