




Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.











NOTES 1 THE RECOMMENDED TIGHTENING TORQUE OF REF. NO. ⑦ TO BE 1 N・m.
COATING WITH LOCTITE 242 MANUFACTURED BY HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT LOOSENESS.
2 CONTACT AREA: GOLD 0.2μm min.
TERMINAL AREA: GOLD FLASH
UNDER PLATING: NICKEL 2μm min.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
4	PHOSPHOR BRONZE	2			
3	PHOSPHOR BRONZE	2	7	BRASS 1	NICKEL PLATING
2	POLYPHENYLENE SULFIDE	(BLACK) 94V-0	6	PHOSPHOR BRONZE	NICKEL PLATING
1	ZINC ALLOY	MATTE FINISH NICKEL PLATING	5	BERYLLIUM COPPER	NICKEL PLATING

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1	2	1	DIS-C-001762	TH. KAMEYA	HY. KISHI	10.06.03

HIROSE ELECTRIC CO., LTD.	APPROVED : MO. SATOH 06.10.03	DRAWING NO.	EDC3-115061-00
	CHECKED : MO. SATOH 06.10.03	PART NO.	HR25A-7R-8S
	DESIGNED : YH. YAMADA 06.10.02	CODE NO.	CL125-0619-0-00
	DRAWN : MK. SATO 06.08.31		2 1/1

HRS DRAWING FOR REFERENCE