

Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


HRS DRAWING FOR REFERENCE

1 Fig.1 THE STATE INCORPORATE APPLICABLE CRIMP CONTACT.



A-A





5 Fig.2 THE APPEARANCE AFTER ASSEMBLY.

NOTES 1 Fig.1 SHOWS THE STATE INCORPORATE APPLICABLE CRIMP CONTACT.
APPLICABLE CRIMP CONTACT :HR41-PC-111
2 APPLICABLE CRIMP CONTACT EXTRACTION TOOL : HR41-TP
3 THE RECOMMENDED TIGHTENING TORQUE OF REF. NO. ③ AND ⑥ TO BE 5 TO 5.5N・m
THE ADHESIVE TOR PREVENTION OF LOOSENESS IS NOT NECESSARY IN THE FIRST TIME.
LOCTITE 263, LOCPRIMER 7649, HENKEL JAPAN IS RECOMMENDED TO PREVENT REF NO. ①, ③ FROM LOOSING. AFTER THE SECOND TIME.
4 ROTATION EXAMPLES ARE SHOWN FOR REF.NO.③ AND ⑥.
5 Fig.2 SHOWS THE APPEARANCE AFTER ASSEMBLY.
6 THE CABLE PULL AND TWISTING STRENGTH AND OTHER CHARACTERISTICS MAY DIFFER, DEPENDING ON THE CABLE STRUCTURE, PLEASE CONFIRM BEFORE THE USE.
7 THE ASSEMBLY OF THIS PRODUCT APPLIES TO THE MANUAL ETAD-C0298.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
3	POLYAMIDE	(BLACK) UL94V-0	6	POLYAMIDE	(BLACK) UL94V-0
2	SILICONE RUBBER	(RED)	5	POLYAMIDE	(WHITE) UL94V-0
1	POLYAMIDE	(BLACK) UL94V-0	4	SILICONE RUBBER	(RED)

UNITS mm	SCALE 1 : 1	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE

HIROSE ELECTRIC CO., LTD.

APPROVED	SU. OBARA	13. 03. 14
CHECKED	HY. KOBAYASHI	13. 03. 14
DESIGNED	TY. SUZUKI	13. 03. 14
DRAWN	KN. IKEHARA	13. 03. 14

DRAWING NO.	EDC3-117998-00
PART NO.	HR41-25WBJB-3PC
CODE NO.	CL141-0017-7-00

1/1