Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	———— °C TO ————°C	STORAGE TEMPERATURE RANGE	———— °C TO ———— °C
	VOLTAGE	————	————	————
	CURRENT	————	APPLICABLE CABLE	————

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
A					

REMARK

Unless otherwise specified, refer to JIS C 5402.

APPROVED	SU.OBARA	12.03.15
CHECKED	HY.KISHI	12.03.15
DESIGNED	DS.MATSUNE	12.03.15
DRAWN	TR.SATO	12.03.14

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

DRAWING NO. ELC4-020707-00

HRS	SPECIFICATION SHEET	PART NO.	HR10A-TC-02	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL150-0041-2-00	A 1/1

FORM HD0011-2-1