







May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



RECOMMENDED PC BOARD HOLE PATTERN



NOTE. PLEASE KEEP THE TOLERANCE TO LESS THAN ± 0.1 FOR THE DIMENSIONS WITHOUT TOLERANCE.

			OVER: Ni 1μm min UNDER: Cu 5μm min					
2	PBT	(BLACK)UL94V-0	5	STEEL				
1	PHOSPHOR BRONZE	CONTACT: Au 0.2μm min	4	STEEL	OVER: Ni 1μm min UNDER: Cu 5μm min			
		LEAD: Au 0.03μm min						
		UNDER: Ni 2μm min	3	PBT	(BLACK)UL94V-0			
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS			
UNITS mm		SCALE 2 : 1		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.		APPROVED : YH. ENAMI	08.06.10	DRAWING NO.	EDC3-009836-02			
		CHECED : HK. TANAKA	08.06.10	PART NO.	SDAB-15P(55)			
		DESIGNED : MT. ITANO	08.06.09	CODE NO.	CL211-0249-9-55			
		DRAWN : MT. ITANO	08.06.09		 1/1			