APPLICA	BLE STANI	DARD								
	OPERATING TEMPERATURE	E RANGE	- 55 °C TO + 65	3° €	STORAGE TEMPERATURE RANGE		E	- 55 °C TO + 65 °C		
RATING	VOLTAGE		_		OPERATING RANGE	HUMIDITY	<i>'</i>	95 % MAX		
	CURRENT		_		APPLICABL	E CABLE	С	CABLE OUTER DIAMETER: φ9mm		
			SPEC	IFICAT	IONS					
	EM		TEST METHOD			RE	QUI	REMENTS	QT	AT
	RUCTION								ı	
					IT. ACCORDING TO DRAWING.			RAWING.	×	×
MARKING		CONFIRMED VISUALLY.							×	×
	NICAL CH		TERISTICS ENDING TO SELL		Luor	244405	<u> </u>	A OLC AND LOOSENESS	1	
VIBRATION		FREQUENCY 10 TO 55 Hz SINGLE AMPLITUDE 0.75 mm, AT 2h, FOR 3 DIRECTIONS.				NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				-
SHOCK			² DURATION OF PULSE 11 MES FOR 3 DIRECTIONS.					×	_	
ENVIRO	NMENTA	L CHA	RACTERISTICS							
RAPID CHAI		TIME	RATURE -55 \rightarrow 5 \sim 35 \rightarrow 65 30 \rightarrow 2 \sim 3 \rightarrow 30 5 CYCLES.		I	AMAGE, C ARTS.	CRA	CK AND LOOSENESS	×	-
COUN	T DE	SCRIPTI	ON OF REVISIONS	D	ESIGNED			CHECKED	DA	ATE
REMARK						APPROV	/ED	DI TAVAVACU	10 1	0 17
						CHECK		RI. TAKAYASU EJ. WAKATSUKI		0. 17
						DESIGN		MO. SHIMOYAMA		0. 17
Unless oth	nerwise spec	cified, re	efer to JIS C 5402.			DRAW	'N	TY. ITO		0. 16
Note QT:Qualification Test AT:Assurance Test X:Applicable Test					DRAWING NO.			ELC4-010051	-01	
HS.	SF	SPECIFICATION SHEET			PART NO.			HDA-CTH (10)		
	HIR	HIROSE ELECTRIC CO., LTD.			CODE NO. CL2		211	-0277-4-10	Δ	1/1