

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our
 Mar.1,2024 Copyright © 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.

COUNT		DESCRIPTION OF REVISIONS		BY	CHKD	DATE	COUNT		DESCRIPTION OF REVISIONS		BY	CHKD	DATE
△							△						
△							△						
APPLICABLE STANDARD													
RATING	OPERATING TEMPERATURE RANGE		— °C TO — °C				STORAGE TEMPERATURE RANGE		— °C TO — °C				
	VOLTAGE		— V AC				CURRENT		— mA				
SPECIFICATIONS													
ITEM		TEST METHOD					REQUIREMENTS					QT	AT
CONSTRUCTION													
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.					ACCORDING TO DRAWING.					○	○
MARKING		CONFIRMED VISUALLY.										○	○
REMARKS													
DRAWN						DESIGNED		CHECKED		APPROVED		RELEASED	
Y. KONDO 01.05.07						Y. KONDO 01.05.07		T. WATANABE 01.05.07		[Signature] 01.5.7			
Unless otherwise specified, refer to JIS C 5402.													
Note QT:Qualification Test AT:Assurance Test ○:Applicable Test													
HRS HIROSE ELECTRIC CO., LTD.						SPECIFICATION SHEET				PART NO. TM-8-DC			
CODE NO.(OLD) CL				DRAWING NO. ELC4-010263				CODE NO. CL222-0276-5				1 1	

FORM No.231-1

