

Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.




A—A





RECOMMENDED PC BOARD HOLE PATTERN


STRAIGHT TYPE, t1.6mm(MOUNTING SIDE)

TOLERANCE HAVE NOT BEEN DESCRIBED TO THE REFERENCE DIMENSION.









HRS DRAWING FOR REFERENCE

NO.	MATERIAL	FINISH , REMARKS
1	PBT	UL94V-0, (GRAY)
2	PHOSPHOR BRONZE	CONTACT AREA : GOLD PLATING 1.27μm MIN. LEAD AREA : GOLD PLATING 0.03μm MIN. UNDER PLATING : NICKEL PLATING 1.27μm MIN.
3	PHOSPHOR BRONZE	SURFACE PLATING : TIN PLATING 3μm MIN. UNDER PLATING : NICKEL PLATING 2μm MIN.

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1					

HIROSE ELECTRIC CO., LTD.

APPROVED	YH. ENAMI	10.02.24
CHECKED	HO. MIWA	10.02.24
DESIGNED	HN. ANDO	10.02.23
DRAWN	HN. ANDO	10.02.23

DRAWING NO.	EDC3-120468-01
PART NO.	TM2RE-1204(50)
CODE NO.	CL222-0592-5-50

1/1