

Apr.1.2021 Copyright 2021 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	— °C TO — °C	STORAGE TEMPERATURE RANGE	— °C TO — °C
	VOLTAGE	— V AC	CURRENT	— mA

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	<input type="radio"/>	<input type="radio"/>
MARKING	CONFIRMED VISUALLY.		<input type="radio"/>	<input type="radio"/>

--	--	--	--

REMARKS	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
	Y. KONDO 99.10.14	Y. KONDO 99.10.14	T. Watanabe 99.10.15	H. Miura 99.10.18	
Unless otherwise specified, refer to JIS C 5402.					

Note QT:Qualification Test AT:Assurance Test ○:Applicable Test					
HRS HIROSE ELECTRIC CO., LTD.		SPECIFICATION SHEET		PART NO. TM-6-DC1	
CODE NO.(OLD) CL	DRAWING NO. ELC4-022875-	CODE NO. CL222-1052-3	1/1		