

Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-10℃ ~ 60℃	STORAGE TEMPERATURE RANGE	-10℃ ~ 60℃	
	POWER	—	CHARACTERISTIC IMPEDANCE	—	
SPECIFICATIONS					
ITEM		TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION					
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING		CONFIRMED VISUALLY.		X	X
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
REMARK			APPROVED	HO. MIWA	06.12.11
			CHECKED	SJ. SHIMIZU	06.12.11
			DESIGNED	TS. ITO	06.12.08
			DRAWN	TS. ITO	06.12.08
Unless otherwise specified, refer to JIS C 5402.					
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.	ELC4-025739-01	
	SPECIFICATION SHEET		PART NO.	TM-4-DC1	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL222-1364-6-00	1/1