

APPLICABLE STANDARD							
RATING	OPERATING TEMPERATURE RANGE		-25°C TO 60°C \triangle	STORAGE TEMPERATURE RANGE		-25°C TO 60°C \triangle	
	VOLTAGE		—	CURRENT		—	
SPECIFICATIONS							
ITEM		TEST METHOD		REQUIREMENTS		QT	AT
CONSTRUCTION							
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		X	X
MARKING		CONFIRMED VISUALLY.				X	X
<div>COUNTDESCRIPTION OF REVISIONSDESIGNEDCHECKEDDATE</div> <div>\triangle3DIS-E-00002932KIM JAEHYEONTU. TANIGUCHI20200403</div>							
REMARK				APPROVED	HO. MIWA	20070214	
				CHECKED	HO. MIWA	20070214	
				DESIGNED	TS. ITO	20070214	
				DRAWN	YK. SATO	20070213	
Unless otherwise specified, refer to IEC 60512. \triangle							
Note QT:Qualification Test AT:Assurance Test X:Applicable Test				DRAWING NO.		ELC-126315-00-00	
<div>HRS</div>		SPECIFICATION SHEET		PART NO.		TM11P1-88P (**)	
		HIROSE ELECTRIC CO., LTD.		CODE NO.		<div>\triangle1/1</div>	