APPLIC/		STANDA	RD									
		ATING ERATURE RA	-25°C TO +60°C				RAGE PERATU	GE RATURE RANGE		−25°C TO +60°C		
RATING	VOLT		_				RRENT					
SPECIFICATIONS												
ITEM TEST METHOD									REQUI	REMENTS	QT	АТ
CONST	RUCT	ION					•					
GENERAL EXAMINATION			VISUALLY AND BY MEASURING INSTRUMENT.					ACCORDING TO DRAWING.				Χ
MARKING			CONFIRMED VISUALLY.								Х	Χ
	ı				1							
COU	NT	DESCI		ON OF REVISIONS						CHECKED	DA	
REMARK			ν1S-l	E-00002925		KIM JAE	EHYEUN	APPRO	OVFD	TU. TANIGUCHI Ho. Miwa	2020	
								CHEC		SJ. SHIMIZU	2006	
								DESIG	NED	TS. ITO	2006	
Unless otherwise specified, refer to IEC 60512. 🛆								DRA	WN	TS. ITO	2006	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test					DRAWING NO.			ELC-120680-13-01				
HS.		SPECIFICATION SHEET				PART NO.			TM11APA-88P (13)			
		HIROS	SE EL	ECTRIC CO., LTD.		CODE	NO.	CL222-2781-9-13		$\Delta$	1/1	