

Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE


PLUG MATED








RECOMMENDED PCB PATTERN (4:1)

(t=1)









NOTES 1 LEAD POSITION FROM BOARD SURFACE 0+0.05/-0.1.
LEAD CO-PLANARITY TO BE 0.1 MAX.
DATUM:A

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
2	PHOSPHOR BRONZE	CONTACT: GOLD PLATING 1.27μm MIN LEAD : TIN PLATING 2μm MIN UNDER :NICKEL PLATING 1μm MIN	4	PS	BLACK, CARBON COATING ANTISTATIC ⚠1
			3	BRASS	OVER : TIN PLATING 2μm MIN UNDER:NICKEL PLATING 1μm MIN
1	PPS	BLACK, UL94V-0			

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2:1	⚠1	2	DIS-E-005039	MT. ITANO	NM. NISHIMATSU	14. 06. 23

HRS HIROSE ELECTRIC CO., LTD.


APPROVED	EJ. WAKATSUKI	14. 06. 05
CHECKED	EJ. WAKATSUKI	14. 06. 05
DESIGNED	MT. ITANO	14. 06. 05
DRAWN	MT. ITANO	14. 06. 05

DRAWING NO.	EDC3-121627-04
PART NO.	TM18R-88(51)
CODE NO.	CL222-2867-2-51 ⚠1 1/2


Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

DRAWING FOR PACKING(1:2)


ANTISTATIC 1



3 C (2:1)



B–B



HRS DRAWING FOR REFERENCE

NOTES. 2. ONE TRAY INCLUDES 50PCS OF PRODUCTS.
3 PRODUCT IS PACKED AS SHOWN IN FIGURE.

HRS	DRAWING NO.	EDC3-121627-04
	PART NO.	TM18R-88(51)
	CODE NO.	CL222-2867-2-51
	1	2/2